

FIG. 1

(REC)	TID	EVENT TYPE	CATEGORY	SOURCE	APPLICATION	HOST	SEVERITY
(1)	1001	TCPConnectionClose	NETWORK	IO	SYSTEM	VESUVIO	LOW
(2)	1001	CiscoDCDLinkUp	NETWORK	DHCP	ROUTING	ETNA	LOW
(3)	1001	AuditFailure	SECURITY	SOFTWARE	AUTHORIZATION	MAGNA	HIGH
(4)	1001	CoreDump	MEMORY	EXCEPTION	KERNEL 2.4	STROMBOLI	HIGH
(5)	1001	IRQConflict	DEVICE	PCI BUS	SYSTEM	VULCANO	HIGH

FIG. 2




FIG. 3




FIG. 4




FIG. 5

τ_1	τ_2	
$t_{11}:A$	$t_{21}:B$	$t_{22}:C$

(a) $c = (A)(BC)$

τ_1	τ_2	
$t_{11}:A$	$t_{21}:B$	$t_{22}:C$

(b) $c_3 = (A)(B)$

τ_1	τ_2	
$t_{11}:A$	$t_{21}:C$	

(c) $c_2 = (A)(C)$

τ_1	τ_2	
$t_{11}:B$	$t_{12}:C$	

(d) $c_1 = (BC)$

FIG. 6

$c = c_L \bowtie c_{L-1}$	c_L	c_{L-1}	MERGE-JOIN?
$(A)(A)(A)$	$(A)(A)$	$(A)(A)$	YES
$(A)(A)(B)$	$(A)(A)$	$(A)(B)$	YES
$(A)(AB)$	$(A)(A)$	$(A)(B)$	NO
$(AB)(B)$	(AB)	$(A)(B)$	YES
$(A)(B)(B)$	$(A)(B)$	$(A)(B)$	YES
$(B)(B)(B)$	$(B)(B)$	$(B)(B)$	YES

FIG. 7

Methodology 1 HIFI(Attributeset: A, Dataset: D, MinSupport: min_sup)
<pre> 1: generate frequent patterns for templates on the 1st level; 2: $L \leftarrow 2$; 3: $Template_L \leftarrow$ pair up templates on the 1st level to generate templates on the 2nd level; 4: $Cand_L \leftarrow$ join patterns on the 1st level to generate candidate patterns on the 2nd level; 5: while $Cand_L \neq \emptyset$ do 6: $countSupport(D, Cand_L)$; 7: eliminate candidates whose support are lower than min_sup; 8: $L \leftarrow L + 1$; 9: $Template_L \leftarrow TemplateGen(Template_{L-1}, A)$; 10: $CandidateGen(Template_L)$; 11: end while 12: return $\{t.patternst \in Template_L\}$; </pre>

FIG. 8






FIG. 9

Methodology 2 countSupport(Dataset: <i>D</i> , PatternSet: <i>candidates</i>)	
1:	for each tuple <i>t</i> $\in D$ do
2:	traverse the item tree to find all items supported by <i>t</i> ;
3:	for each <i>item</i> supported by <i>t</i> do
4:	record the current TID and RID in <i>item</i> 's occurrence buffer;
5:	end for
6:	if any occurrence buffer is full then
7:	for each pattern <i>p</i> \in <i>candidates</i> do
8:	scan the occurrence buffer of each item in <i>p</i> (scan is synchronized by TID), and increase the count of <i>p</i> if each item of <i>p</i> is supported by a different record (of the same TID);
9:	end for
10:	empty all occurrence buffers;
11:	end if
12:	end for



FIG. 10

Methodology 3 TemplateGen(SetOfTemplates: <i>parentTemplates</i>)	
1:	<i>Templates</i> $\leftarrow \emptyset$;
2:	for each $p \in \text{parentTemplates}$ do
3:	for each child template c of p do
4:	$\text{Templates} \leftarrow \text{Templates} \cup \{c\}$ if all of c 's parent templates exist and have non-empty pattern set;
5:	prune <i>Templates</i> using user preferences;
6:	end for
7:	end for
8:	return <i>Templates</i> ;

FIG. 11




FIG. 12

